Appendix B

ST. MARY PARISH ONROAD MOBILE
EMISSION SUMMARIES

Including:
MOBILE6 Input and Output Files for
2002, 2008, 2011, and 2014; RVP 7.8

2002 ACTUAL ON-ROAD MOBILE EMISSIONS INVENTORY
ST. MARY PARISH
PEAK OZONE SEASON, RVP 7.8

ROAD CLASS	SPEED (MPH)	VOC (G/MI)	NOx (G/MI)	VMT (MI/DAY)	VOC (TPD)	NOx (TPD)
01	63.0	1.191	4.832	0	0.00	0.00
02	58.5	1.266	2.594	754,673	1.05	2.16
06	49.5	1.316	2.120	0	0.00	0.00
07	45.0	1.361	1.787	328,470	0.49	0.65
08	36.0	1.446	1.814	76,330	0.12	0.15
09	27.0	2.269	1.814	66,367	0.17	0.13
11	58.5	1.273	2.513	0	0.00	0.00
12	58.5	1.293	2.069	43,808	0.06	0.10
14	49.5	1.343	1.649	27,131	0.04	0.05
16	45.0	1.384	1.467	153,685	0.23	0.25
17	36.0	1.465	1.405	42,090	0.07	0.07
19	27.0	2.269	1.320	14,751	0.04	0.02
				1,507,306	2.28	3.57

ROADWAY FUNCTIONAL CLASS CODE

01 - RURAL PRINCIPAL ARTERIAL, INTERSTATE
02 - RURAL PRINCIPAL ARTERIAL, OTHER
06 - RURAL MINOR ARTERIAL
07 - RURAL MAJOR COLLECTOR
08 - RURAL MINOR COLLECTOR
09 - RURAL LOCAL ROAD

11 - URBAN PRINCIPAL ARTERIAL, INTERSTATE
12 - URBAN PRINCIPAL ARTERIAL, FREEWAY
14 - URBAN PRINCIPAL ARTERIAL, OTHER
16 - URBAN MINOR ARTERIAL
17 - URBAN COLLECTOR
19 - URBAN LOCAL ROAD

LDEQ, OEA, 3/31/2006

```
* St. Mary Parish; Ozone Season, 2002
******************  Header Section  ************************
MOBILE6 INPUT FILE :
POLLUTANTS         : HC NOX
RUN DATA
******************  Run Section  ***************************
>Year 2002 - St. Mary Parish Emission Factors
NO REFUELING       :
MIN/MAX TEMP       : 72.9 90.2
ABSOLUTE HUMIDITY  : 150.5
FUEL RVP           : 7.8
REG DIST           : LA_REGD.D
ANTI-TAMP PROG     : 00 80 95 22222 21111111 1 11 072. 22222222
******************  Scenario Section  **********************
SCENARIO REC       : Rural interstate, 63.0
CALENDAR YEAR      : 2002
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 63.0 Non-Ramp 100.0 0.0 0.0 0.0
VMT FRACTIONS      :
0.599  0.038  0.127  0.014  0.007  0.068  0.007  0.005
0.004  0.015  0.017  0.019  0.069  0.003  0.002  0.006
******************  Scenario Section  **********************
SCENARIO REC       : Rural principal arterial, 58.5
CALENDAR YEAR      : 2002
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 58.5 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.652  0.048  0.160  0.016  0.008  0.036  0.004  0.003
0.002  0.008  0.009  0.010  0.037  0.002  0.001  0.004
******************  Scenario Section  **********************
SCENARIO REC       : Rural minor arterial, 49.5
CALENDAR YEAR      : 2002
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 49.5 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.672  0.046  0.155  0.017  0.008  0.032  0.003  0.002
0.002  0.007  0.008  0.009  0.032  0.002  0.001  0.004
******************  Scenario Section  **********************
SCENARIO REC       : Rural major collector, 45.0
CALENDAR YEAR      : 2002
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 45.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.667  0.054  0.178  0.017  0.008  0.023  0.002  0.002
0.001  0.005  0.006  0.007  0.024  0.001  0.001  0.004
******************  Scenario Section  **********************
SCENARIO REC       : Rural minor collector, 36.0
CALENDAR YEAR      : 2002
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 36.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.639  0.056  0.186  0.009  0.004  0.027  0.003  0.002
0.002  0.006  0.007  0.008  0.027  0.001  0.001  0.022
******************  Scenario Section  **********************
SCENARIO REC       : Rural local, 27.0
CALENDAR YEAR      : 2002
EVALUATION MONTH   : 7
ALTITUDE           : 1
VMT BY FACILITY    : localvmt.d
VMT FRACTIONS      :
0.654  0.057  0.189  0.003  0.002  0.024  0.002  0.002
0.001  0.005  0.006  0.007  0.025  0.001  0.001  0.021
******************  Scenario Section  **********************
SCENARIO REC       : Urban interstate, 58.5
CALENDAR YEAR      : 2002
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 58.5 Non-Ramp 100.0 0.0 0.0 0.0
VMT FRACTIONS      :
0.720  0.037  0.122  0.019  0.009  0.030  0.003  0.002
0.002  0.006  0.008  0.008  0.030  0.001  0.001  0.002
******************  Scenario Section  **********************
SCENARIO REC       : Urban other expressway, 58.5
CALENDAR YEAR      : 2002
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 58.5 Non-Ramp 100.0 0.0 0.0 0.0
VMT FRACTIONS      :
0.764  0.034  0.112  0.018  0.008  0.020  0.002  0.002
```

```
0.001  0.004  0.005  0.006  0.021  0.001  0.000  0.002
*******************  Scenario Section  ************************
SCENARIO REC        : Urban principal arterial, 49.5
CALENDAR YEAR       : 2002
EVALUATION MONTH    : 7
ALTITUDE            : 1
AVERAGE SPEED       : 49.5 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS       :
0.766  0.034  0.113  0.018  0.008  0.018  0.002  0.001
0.001  0.004  0.005  0.005  0.018  0.001  0.000  0.006
*******************  Scenario Section  ************************
SCENARIO REC        : Urban minor arterial, 45.0
CALENDAR YEAR       : 2002
EVALUATION MONTH    : 7
ALTITUDE            : 1
AVERAGE SPEED       : 45.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS       :
0.773  0.040  0.131  0.009  0.004  0.013  0.001  0.001
0.001  0.003  0.003  0.004  0.014  0.001  0.000  0.002
*******************  Scenario Section  ************************
SCENARIO REC        : Urban collector, 36.0
CALENDAR YEAR       : 2002
EVALUATION MONTH    : 7
ALTITUDE            : 1
AVERAGE SPEED       : 36.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS       :
0.772  0.037  0.125  0.007  0.003  0.013  0.001  0.001
0.001  0.003  0.003  0.004  0.013  0.001  0.000  0.016
*******************  Scenario Section  ************************
SCENARIO REC        : Urban local, 27.0
CALENDAR YEAR       : 2002
EVALUATION MONTH    : 7
ALTITUDE            : 1
VMT BY FACILITY     : localvmt.d
VMT FRACTIONS       :
0.797  0.037  0.122  0.003  0.001  0.008  0.001  0.001
0.000  0.002  0.002  0.002  0.009  0.000  0.000  0.015

END OF RUN
```

```
*************************************************************************
* MOBILE6.2.03 (24-Sep-2003)                                            *
* Input file: C:\MOBILE6\RUN\110A1\LIMITED\22101_02.IN (file 1, run 1).  *
*************************************************************************
*Year 2002 - St. Mary Parish Emission Factors
  M603 Comment:
               User has disabled the calculation of REFUELING emissions.


* Reading Registration Distributions from the following external
* data file: LA_REGD.D

* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural interstate, 63.0
* File 1, Run 1, Scenario 1.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M581 Warning:
            The user supplied freeway average speed of 63.0
            will be used for all hours of the day. 100% of VMT
            has been assigned to the freeway roadway type for
            all hours of the day and all vehicle types.
  M615 Comment:
               User supplied VMT mix.
  M 48 Warning:
              there are no sales for vehicle class HDGV8b

                    Calendar Year:  2002
                            Month:  July
                         Altitude:  Low
              Minimum Temperature:  72.9 (F)
              Maximum Temperature:  90.2 (F)
                Absolute Humidity:  151. grains/lb
                 Nominal Fuel RVP:   7.8 psi
                    Weathered RVP:   7.5 psi
              Fuel Sulfur Content:  279. ppm

              Exhaust I/M Program:  No
                 Evap I/M Program:  No
                       ATP Program:  Yes
                 Reformulated Gas:  No
```

Vehicle Type:	LDGV	LDGT12	LDGT34	LDGT	HDGV	LDDV	LDDT	HDDV	MC	All Veh
GVWR:		<6000	>6000	(All)						
VMT Distribution:	0.5978	0.1648	0.0207		0.0633	0.0012	0.0005	0.1457	0.0060	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	1.326	1.365	0.859	1.309	1.149	0.663	1.121	0.441	2.97	1.191
Composite NOX :	1.088	1.175	1.165	1.174	5.996	2.576	2.896	24.517	1.36	4.832

```
* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural principal arterial, 58.5
* File 1, Run 1, Scenario 2.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 58.5
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
               User supplied VMT mix.
  M 48 Warning:
              there are no sales for vehicle class HDGV8b
```

```
              Calendar Year:  2002
                      Month:  July
                   Altitude:  Low
     Minimum Temperature:  72.9 (F)
     Maximum Temperature:  90.2 (F)
       Absolute Humidity:  151. grains/lb
        Nominal Fuel RVP:   7.8 psi
           Weathered RVP:   7.5 psi
     Fuel Sulfur Content:  279. ppm

     Exhaust I/M Program:  No
        Evap I/M Program:  No
             ATP Program:  Yes
        Reformulated Gas:  No
```

Vehicle Type: GVWR:	LDGV	LDGT12 <6000	LDGT34 >6000	LDGT (All)	HDGV	LDDV	LDDT	HDDV	MC	All Veh
VMT Distribution:	0.6507	0.2078	0.0236		0.0337	0.0013	0.0006	0.0783	0.0040	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	1.340	1.384	0.865	1.331	1.172	0.665	1.173	0.443	2.65	1.266
Composite NOX :	1.075	1.156	1.146	1.155	5.838	2.176	2.505	18.150	1.27	2.594

```
* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural minor arterial, 49.5
* File 1, Run 1, Scenario 3.
* # # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
          The user supplied arterial average speed of 49.5
          will be used for all hours of the day.  100% of VMT
          has been assigned to the arterial/collector roadway
          type for all hours of the day and all vehicle types.
  M615 Comment:
           User supplied VMT mix.
  M 48 Warning:
          there are no sales for vehicle class HDGV8b

              Calendar Year:  2002
                      Month:  July
                   Altitude:  Low
     Minimum Temperature:  72.9 (F)
     Maximum Temperature:  90.2 (F)
       Absolute Humidity:  151. grains/lb
        Nominal Fuel RVP:   7.8 psi
           Weathered RVP:   7.5 psi
     Fuel Sulfur Content:  279. ppm

     Exhaust I/M Program:  No
        Evap I/M Program:  No
             ATP Program:  Yes
        Reformulated Gas:  No
```

Vehicle Type: GVWR:	LDGV	LDGT12 <6000	LDGT34 >6000	LDGT (All)	HDGV	LDDV	LDDT	HDDV	MC	All Veh
VMT Distribution:	0.6707	0.2008	0.0246		0.0299	0.0013	0.0006	0.0681	0.0040	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	1.381	1.430	0.882	1.370	1.244	0.685	1.163	0.475	2.41	1.316
Composite NOX :	1.053	1.120	1.103	1.118	5.491	1.691	1.923	14.529	1.08	2.120

```
* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural major collector, 45.0
* File 1, Run 1, Scenario 4.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 45.0
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
               User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b

                   Calendar Year:  2002
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:  279. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No
```

Vehicle Type: GVWR:	LDGV	LDGT12 <6000	LDGT34 >6000	LDGT (All)	HDGV	LDDV	LDDT	HDDV	MC	All Veh
VMT Distribution:	0.6657	0.2318	0.0246		0.0212	0.0013	0.0006	0.0508	0.0040	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	1.408	1.457	0.893	1.402	1.298	0.705	1.265	0.507	2.43	1.361
Composite NOX :	1.043	1.101	1.085	1.099	5.298	1.555	1.831	13.600	1.02	1.787

```
* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural minor collector, 36.0
* File 1, Run 1, Scenario 5.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 36.0
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
               User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b

                   Calendar Year:  2002
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:  279. ppm
```

```
              Exhaust I/M Program:  No
                 Evap I/M Program:  No
                      ATP Program:  Yes
                 Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                       ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:    0.6378    0.2418    0.0128              0.0254    0.0012    0.0004    0.0586    0.0220    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      1.470     1.513     0.917     1.483     1.522     0.771     1.761     0.596      2.56     1.446
    Composite NOX :      1.029     1.072     1.051     1.071     4.970     1.440     1.983    12.526      0.99     1.814
  ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural local, 27.0
* File 1, Run 1, Scenario 6.
* # # # # # # # # # # # # # # # # # # # # # # # # # #

* Reading Hourly Roadway VMT distribution from the following external
* data file: LOCALVMT.D

  Reading User Supplied ROADWAY VMT Factors
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
              there are no sales for vehicle class HDGV8b

                    Calendar Year:  2002
                            Month:  July
                         Altitude:  Low
              Minimum Temperature:  72.9 (F)
              Maximum Temperature:  90.2 (F)
                Absolute Humidity:  151. grains/lb
                 Nominal Fuel RVP:   7.8 psi
                    Weathered RVP:   7.5 psi
              Fuel Sulfur Content:  279. ppm

              Exhaust I/M Program:  No
                 Evap I/M Program:  No
                      ATP Program:  Yes
                 Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                       ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:    0.6527    0.2458    0.0049              0.0220    0.0013    0.0003    0.0520    0.0210    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      2.256     2.258     1.440     2.242     3.784     1.248     3.214     1.309      3.82     2.269
    Composite NOX :      1.079     1.049     1.057     1.049     4.064     1.918     3.063    14.161      0.80     1.814
  ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban interstate, 58.5
* File 1, Run 1, Scenario 7.
* # # # # # # # # # # # # # # # # # # # # # # # # # #
  M581 Warning:
             The user supplied freeway average speed of 58.5
             will be used for all hours of the day. 100% of VMT
             has been assigned to the freeway roadway type for
             all hours of the day and all vehicle types.
  M615 Comment:
```

```
              User supplied VMT mix.
M 48 Warning:
             there are no sales for vehicle class HDGV8b

                   Calendar Year:  2002
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:  279. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                       ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:    0.7186    0.1588    0.0276              0.0278    0.0014    0.0006    0.0632    0.0020    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
Composite Emission Factors (g/mi):
    Composite VOC :     1.340     1.384     0.865     1.307     1.144     0.665     0.971     0.444      2.65     1.273
    Composite NOX :     1.075     1.156     1.142     1.154     5.813     2.176     2.285    21.465      1.27     2.513
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban other expressway, 58.5
* File 1, Run 1, Scenario 8.
* # # # # # # # # # # # # # # # # # # # # # # # # # # #
M581 Warning:
           The user supplied freeway average speed of 58.5
           will be used for all hours of the day. 100% of VMT
           has been assigned to the freeway roadway type for
           all hours of the day and all vehicle types.
M615 Comment:
              User supplied VMT mix.
M 48 Warning:
             there are no sales for vehicle class HDGV8b

                   Calendar Year:  2002
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:  279. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                       ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:    0.7625    0.1459    0.0256              0.0185    0.0015    0.0005    0.0435    0.0020    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
Composite Emission Factors (g/mi):
```

```
    Composite VOC :      1.340     1.384     0.864     1.306     1.166     0.665     0.966     0.443      2.65     1.293
    Composite NOX :      1.075     1.156     1.138     1.153     5.825     2.176     2.280    21.524      1.27     2.069
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban principal arterial, 49.5
* File 1, Run 1, Scenario 9.
* # # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 49.5
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
             User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b

                  Calendar Year:  2002
                          Month:  July
                       Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:  279. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No

       Vehicle Type:      LDGV     LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:                 <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
   VMT Distribution:    0.7645    0.1469    0.0256              0.0168    0.0015    0.0005    0.0382    0.0060    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      1.381     1.430     0.881     1.349     1.240     0.685     0.995     0.473      2.41     1.343
    Composite NOX :      1.053     1.119     1.099     1.116     5.490     1.691     1.778    14.386      1.08     1.649
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban minor arterial, 45.0
* File 1, Run 1, Scenario 10.
* # # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 45.0
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
             User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b

                  Calendar Year:  2002
                          Month:  July
                       Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
```

```
              Weathered RVP:   7.5 psi
        Fuel Sulfur Content:  279. ppm

        Exhaust I/M Program:  No
           Evap I/M Program:  No
                ATP Program:  Yes
           Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                       ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:    0.7715    0.1708    0.0128              0.0123    0.0015    0.0004    0.0287    0.0020    1.0000
 ---------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      1.408     1.456     0.892     1.417     1.338     0.705     1.457     0.507      2.43     1.384
    Composite NOX :      1.043     1.101     1.081     1.099     5.338     1.555     1.982    13.580      1.02     1.467
 ---------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban collector, 36.0
* File 1, Run 1, Scenario 11.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
           The user supplied arterial average speed of 36.0
           will be used for all hours of the day.  100% of VMT
           has been assigned to the arterial/collector roadway
           type for all hours of the day and all vehicle types.
  M615 Comment:
            User supplied VMT mix.
  M 48 Warning:
            there are no sales for vehicle class HDGV8b

                 Calendar Year:  2002
                         Month:  July
                      Altitude:  Low
            Minimum Temperature:  72.9 (F)
            Maximum Temperature:  90.2 (F)
              Absolute Humidity:  151. grains/lb
               Nominal Fuel RVP:   7.8 psi
                  Weathered RVP:   7.5 psi
            Fuel Sulfur Content:  279. ppm

            Exhaust I/M Program:  No
               Evap I/M Program:  No
                    ATP Program:  Yes
               Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                       ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:    0.7705    0.1618    0.0099              0.0123    0.0015    0.0003    0.0277    0.0160    1.0000
 ---------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      1.470     1.513     0.917     1.479     1.565     0.771     1.680     0.598      2.56     1.465
    Composite NOX :      1.029     1.072     1.048     1.071     4.995     1.440     1.926    12.548      0.99     1.405
 ---------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban local, 27.0
* File 1, Run 1, Scenario 12.
* # # # # # # # # # # # # # # # # # # # # # # # # #

* Reading Hourly Roadway VMT distribution from the following external
* data file: LOCALVMT.D
```

```
Reading User Supplied ROADWAY VMT Factors
M615 Comment:
            User supplied VMT mix.
M 48 Warning:
           there are no sales for vehicle class HDGV8b

                Calendar Year:  2002
                        Month:  July
                     Altitude:  Low
           Minimum Temperature:  72.9 (F)
           Maximum Temperature:  90.2 (F)
             Absolute Humidity:  151. grains/lb
              Nominal Fuel RVP:   7.8 psi
                 Weathered RVP:   7.5 psi
           Fuel Sulfur Content:  279. ppm

           Exhaust I/M Program:  No
              Evap I/M Program:  No
                   ATP Program:  Yes
              Reformulated Gas:  No
```

Vehicle Type: GVWR:	LDGV	LDGT12 <6000	LDGT34 >6000	LDGT (All)	HDGV	LDDV	LDDT	HDDV	MC	All Veh
VMT Distribution:	0.7955	0.1588	0.0039		0.0073	0.0015	0.0002	0.0177	0.0150	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	2.256	2.258	1.426	2.237	3.691	1.248	3.091	1.295	3.82	2.269
Composite NOX :	1.079	1.048	1.010	1.047	4.042	1.918	2.978	13.877	0.80	1.320

2008 PROJECTED ON-ROAD MOBILE EMISSIONS INVENTORY
ST. MARY PARISH
PEAK OZONE SEASON, RVP 7.8

ROAD CLASS	SPEED (MPH)	VOC (G/MI)	NOx (G/MI)	VMT (MI/DAY)	VOC (TPD)	NOx (TPD)
01	63.0	0.679	2.704	0	0.00	0.00
02	58.5	0.719	1.509	869,600	0.69	1.45
06	49.5	0.755	1.215	0	0.00	0.00
07	45.0	0.784	1.020	378,492	0.33	0.43
08	36.0	0.860	1.040	87,954	0.08	0.10
09	27.0	1.332	1.096	66,367	0.10	0.08
11	58.5	0.719	1.393	0	0.00	0.00
12	58.5	0.730	1.146	51,073	0.04	0.06
14	49.5	0.771	0.939	31,631	0.03	0.03
16	45.0	0.794	0.832	172,270	0.15	0.16
17	36.0	0.864	0.800	42,699	0.04	0.04
19	27.0	1.323	0.776	14,751	0.02	0.01
				1,714,838	1.48	2.36

ROADWAY FUNCTIONAL CLASS CODE

01 - RURAL PRINCIPAL ARTERIAL, INTERSTATE
02 - RURAL PRINCIPAL ARTERIAL, OTHER
06 - RURAL MINOR ARTERIAL
07 - RURAL MAJOR COLLECTOR
08 - RURAL MINOR COLLECTOR
09 - RURAL LOCAL ROAD

11 - URBAN PRINCIPAL ARTERIAL, INTERSTATE
12 - URBAN PRINCIPAL ARTERIAL, FREEWAY
14 - URBAN PRINCIPAL ARTERIAL, OTHER
16 - URBAN MINOR ARTERIAL
17 - URBAN COLLECTOR
19 - URBAN LOCAL ROAD

LDEQ, OEA, 3/31/2006

```
* St. Mary Parish; Ozone Season, 2008
******************  Header Section  ************************
MOBILE6 INPUT FILE :
POLLUTANTS         : HC NOX
RUN DATA
******************  Run Section  ***************************
>Year 2008 - St. Mary Parish Emission Factors
NO REFUELING       :
MIN/MAX TEMP       : 72.9 90.2
ABSOLUTE HUMIDITY  : 150.5
FUEL RVP           : 7.8
REG DIST           : LA_REGD.D
ANTI-TAMP PROG     : 00 80 95 22222 21111111 1 11 072. 22222222
******************  Scenario Section  ************************
SCENARIO REC       : Rural interstate, 63.0
CALENDAR YEAR      : 2008
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 63.0 Non-Ramp 100.0 0.0 0.0 0.0
VMT FRACTIONS      :
0.599  0.038  0.127  0.014  0.007  0.068  0.007  0.005
0.004  0.015  0.017  0.019  0.069  0.003  0.002  0.006
******************  Scenario Section  ************************
SCENARIO REC       : Rural principal arterial, 58.5
CALENDAR YEAR      : 2008
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 58.5 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.652  0.048  0.160  0.016  0.008  0.036  0.004  0.003
0.002  0.008  0.009  0.010  0.037  0.002  0.001  0.004
******************  Scenario Section  ************************
SCENARIO REC       : Rural minor arterial, 49.5
CALENDAR YEAR      : 2008
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 49.5 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.672  0.046  0.155  0.017  0.008  0.032  0.003  0.002
0.002  0.007  0.008  0.009  0.032  0.002  0.001  0.004
******************  Scenario Section  ************************
SCENARIO REC       : Rural major collector, 45.0
CALENDAR YEAR      : 2008
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 45.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.667  0.054  0.178  0.017  0.008  0.023  0.002  0.002
0.001  0.005  0.006  0.007  0.024  0.001  0.001  0.004
******************  Scenario Section  ************************
SCENARIO REC       : Rural minor collector, 36.0
CALENDAR YEAR      : 2008
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 36.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.639  0.056  0.186  0.009  0.004  0.027  0.003  0.002
0.002  0.006  0.007  0.008  0.027  0.001  0.001  0.022
******************  Scenario Section  ************************
SCENARIO REC       : Rural local, 27.0
CALENDAR YEAR      : 2008
EVALUATION MONTH   : 7
ALTITUDE           : 1
VMT BY FACILITY    : localvmt.d
VMT FRACTIONS      :
0.654  0.057  0.189  0.003  0.002  0.024  0.002  0.002
0.001  0.005  0.006  0.007  0.025  0.001  0.001  0.021
******************  Scenario Section  ************************
SCENARIO REC       : Urban interstate, 58.5
CALENDAR YEAR      : 2008
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 58.5 Non-Ramp 100.0 0.0 0.0 0.0
VMT FRACTIONS      :
0.720  0.037  0.122  0.019  0.009  0.030  0.003  0.002
0.002  0.006  0.008  0.008  0.030  0.001  0.001  0.002
******************  Scenario Section  ************************
SCENARIO REC       : Urban other expressway, 58.5
CALENDAR YEAR      : 2008
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 58.5 Non-Ramp 100.0 0.0 0.0 0.0
VMT FRACTIONS      :
0.764  0.034  0.112  0.018  0.008  0.020  0.002  0.002
```

```
0.001  0.004  0.005  0.006  0.021  0.001  0.000  0.002
******************   Scenario Section   ************************
SCENARIO REC        : Urban principal arterial, 49.5
CALENDAR YEAR       : 2008
EVALUATION MONTH    : 7
ALTITUDE            : 1
AVERAGE SPEED       : 49.5 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS       :
0.766  0.034  0.113  0.018  0.008  0.018  0.002  0.001
0.001  0.004  0.005  0.005  0.018  0.001  0.000  0.006
******************   Scenario Section   ************************
SCENARIO REC        : Urban minor arterial, 45.0
CALENDAR YEAR       : 2008
EVALUATION MONTH    : 7
ALTITUDE            : 1
AVERAGE SPEED       : 45.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS       :
0.773  0.040  0.131  0.009  0.004  0.013  0.001  0.001
0.001  0.003  0.003  0.004  0.014  0.001  0.000  0.002
******************   Scenario Section   ************************
SCENARIO REC        : Urban collector, 36.0
CALENDAR YEAR       : 2008
EVALUATION MONTH    : 7
ALTITUDE            : 1
AVERAGE SPEED       : 36.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS       :
0.772  0.037  0.125  0.007  0.003  0.013  0.001  0.001
0.001  0.003  0.003  0.004  0.013  0.001  0.000  0.016
******************   Scenario Section   ************************
SCENARIO REC        : Urban local, 27.0
CALENDAR YEAR       : 2008
EVALUATION MONTH    : 7
ALTITUDE            : 1
VMT BY FACILITY     : localvmt.d
VMT FRACTIONS       :
0.797  0.037  0.122  0.003  0.001  0.008  0.001  0.001
0.000  0.002  0.002  0.002  0.009  0.000  0.000  0.015

END OF RUN
```

```
*************************************************************************
* MOBILE6.2.03 (24-Sep-2003)                                            *
* Input file: C:\MOBILE6\RUN\110A1\LIMITED\22101_08.IN (file 1, run 1). *
*************************************************************************
*Year 2008 - St. Mary Parish Emission Factors
  M603 Comment:
              User has disabled the calculation of REFUELING emissions.


* Reading Registration Distributions from the following external
* data file: LA_REGD.D

* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural interstate, 63.0
* File 1, Run 1, Scenario 1.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M581 Warning:
            The user supplied freeway average speed of 63.0
            will be used for all hours of the day. 100% of VMT
            has been assigned to the freeway roadway type for
            all hours of the day and all vehicle types.
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b

                   Calendar Year:  2008
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No
```

Vehicle Type: GVWR:	LDGV	LDGT12 <6000	LDGT34 >6000	LDGT (All)	HDGV	LDDV	LDDT	HDDV	MC	All Veh
VMT Distribution:	0.5984	0.1650	0.0207		0.0622	0.0006	0.0003	0.1468	0.0060	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	0.737	0.776	0.463	0.741	0.662	0.311	0.315	0.284	2.91	0.679
Composite NOX :	0.604	0.725	0.706	0.723	3.532	1.299	1.033	13.490	1.36	2.704

```
* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural principal arterial, 58.5
* File 1, Run 1, Scenario 2.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 58.5
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b
```

```
                Calendar Year:  2008
                        Month:  July
                     Altitude:  Low
        Minimum Temperature:  72.9 (F)
        Maximum Temperature:  90.2 (F)
          Absolute Humidity:  151. grains/lb
           Nominal Fuel RVP:   7.8 psi
              Weathered RVP:   7.5 psi
        Fuel Sulfur Content:   30. ppm

        Exhaust I/M Program:  No
           Evap I/M Program:  No
                ATP Program:  Yes
           Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.6513    0.2080    0.0236              0.0331    0.0007    0.0004    0.0789    0.0040    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      0.750     0.788     0.470     0.756     0.674     0.312     0.326     0.286      2.60     0.719
    Composite NOX :      0.597     0.714     0.695     0.712     3.440     1.097     0.883    10.586      1.27     1.509
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural minor arterial, 49.5
* File 1, Run 1, Scenario 3.
* # # # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 49.5
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b

                Calendar Year:  2008
                        Month:  July
                     Altitude:  Low
        Minimum Temperature:  72.9 (F)
        Maximum Temperature:  90.2 (F)
          Absolute Humidity:  151. grains/lb
           Nominal Fuel RVP:   7.8 psi
              Weathered RVP:   7.5 psi
        Fuel Sulfur Content:   30. ppm

        Exhaust I/M Program:  No
           Evap I/M Program:  No
                ATP Program:  Yes
           Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.6713    0.2010    0.0246              0.0293    0.0007    0.0004    0.0687    0.0040    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      0.783     0.821     0.488     0.785     0.717     0.322     0.330     0.307      2.35     0.755
    Composite NOX :      0.583     0.692     0.670     0.689     3.239     0.853     0.678     8.266      1.08     1.215
 ---------------------------------------------------------------------------------------------------------------------------
```

```
* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural major collector, 45.0
* File 1, Run 1, Scenario 4.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 45.0
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
             User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b

                  Calendar Year:  2008
                          Month:  July
                       Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No

       Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:                <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.6663    0.2320    0.0246              0.0208    0.0007    0.0004    0.0512    0.0040    1.0000
  ---------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
     Composite VOC :      0.804     0.839     0.499     0.806     0.745     0.332     0.355     0.325      2.37     0.784
     Composite NOX :      0.578     0.680     0.660     0.678     3.120     0.784     0.636     7.646      1.02     1.020
  ---------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural minor collector, 36.0
* File 1, Run 1, Scenario 5.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 36.0
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
             User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b

                  Calendar Year:  2008
                          Month:  July
                       Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm
```

```
              Exhaust I/M Program:  No
                 Evap I/M Program:  No
                      ATP Program:  Yes
                 Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34     LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.6383    0.2420    0.0128              0.0250    0.0007    0.0002    0.0590    0.0220    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
     Composite VOC :      0.849     0.877     0.522     0.859     0.856     0.363     0.497     0.383      2.50     0.860
     Composite NOX :      0.570     0.663     0.641     0.662     2.928     0.726     0.675     6.974      0.99     1.040
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural local, 27.0
* File 1, Run 1, Scenario 6.
* # # # # # # # # # # # # # # # # # # # # # # # # # #

* Reading Hourly Roadway VMT distribution from the following external
* data file: LOCALVMT.D

  Reading User Supplied ROADWAY VMT Factors
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
              there are no sales for vehicle class HDGV8b

                    Calendar Year:  2008
                            Month:  July
                         Altitude:  Low
              Minimum Temperature:  72.9 (F)
              Maximum Temperature:  90.2 (F)
                Absolute Humidity:  151. grains/lb
                 Nominal Fuel RVP:   7.8 psi
                    Weathered RVP:   7.5 psi
              Fuel Sulfur Content:   30. ppm

              Exhaust I/M Program:  No
                 Evap I/M Program:  No
                      ATP Program:  Yes
                 Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34     LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.6533    0.2460    0.0049              0.0216    0.0007    0.0001    0.0524    0.0210    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
     Composite VOC :      1.293     1.292     0.823     1.283     1.932     0.592     1.153     0.840      3.76     1.332
     Composite NOX :      0.610     0.666     0.672     0.666     2.393     0.967     1.195     8.802      0.80     1.096
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban interstate, 58.5
* File 1, Run 1, Scenario 7.
* # # # # # # # # # # # # # # # # # # # # # # # # # #
  M581 Warning:
            The user supplied freeway average speed of 58.5
            will be used for all hours of the day. 100% of VMT
            has been assigned to the freeway roadway type for
            all hours of the day and all vehicle types.
  M615 Comment:
```

```
              User supplied VMT mix.
M 48 Warning:
             there are no sales for vehicle class HDGV8b

                   Calendar Year:  2008
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:                <6000     >6000     (All)
                       ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:    0.7192    0.1590    0.0276              0.0274    0.0008    0.0004    0.0636    0.0020    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      0.750     0.788     0.470     0.741     0.664     0.312     0.291     0.285      2.60     0.719
    Composite NOX :      0.597     0.713     0.692     0.710     3.423     1.097     0.840    11.538      1.27     1.393
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban other expressway, 58.5
* File 1, Run 1, Scenario 8.
* # # # # # # # # # # # # # # # # # # # # # # # # # #
  M581 Warning:
            The user supplied freeway average speed of 58.5
            will be used for all hours of the day. 100% of VMT
            has been assigned to the freeway roadway type for
            all hours of the day and all vehicle types.
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b

                   Calendar Year:  2008
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:                <6000     >6000     (All)
                       ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:    0.7632    0.1460    0.0256              0.0182    0.0008    0.0004    0.0438    0.0020    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
```

```
    Composite VOC :      0.750     0.788     0.469     0.741     0.672     0.312     0.291     0.287      2.60     0.730
    Composite NOX :      0.597     0.713     0.689     0.710     3.430     1.097     0.839    11.484      1.27     1.146
  ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban principal arterial, 49.5
* File 1, Run 1, Scenario 9.
* # # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 49.5
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
             User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b

                  Calendar Year:  2008
                          Month:  July
                       Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No

       Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.7652    0.1470    0.0256              0.0165    0.0008    0.0004    0.0385    0.0060    1.0000
  ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      0.783     0.821     0.488     0.771     0.713     0.322     0.302     0.307      2.35     0.771
    Composite NOX :      0.583     0.691     0.668     0.688     3.234     0.853     0.650     8.142      1.08     0.939
  ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban minor arterial, 45.0
* File 1, Run 1, Scenario 10.
* # # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 45.0
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
             User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b

                  Calendar Year:  2008
                          Month:  July
                       Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
```

```
           Weathered RVP:   7.5 psi
     Fuel Sulfur Content:   30. ppm

     Exhaust I/M Program:  No
        Evap I/M Program:  No
             ATP Program:  Yes
        Reformulated Gas:  No
```

Vehicle Type: GVWR:	LDGV	LDGT12 <6000	LDGT34 >6000	LDGT (All)	HDGV	LDDV	LDDT	HDDV	MC	All Veh
VMT Distribution:	0.7722	0.1710	0.0128		0.0120	0.0008	0.0002	0.0290	0.0020	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	0.804	0.839	0.499	0.815	0.766	0.332	0.398	0.329	2.37	0.794
Composite NOX :	0.578	0.680	0.658	0.679	3.154	0.784	0.676	7.594	1.02	0.832

```
* # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban collector, 36.0
* File 1, Run 1, Scenario 11.
* # # # # # # # # # # # # # # # # # # # # # # # # #
 M583 Warning:
           The user supplied arterial average speed of 36.0
           will be used for all hours of the day.  100% of VMT
           has been assigned to the arterial/collector roadway
           type for all hours of the day and all vehicle types.
 M615 Comment:
              User supplied VMT mix.
 M 48 Warning:
             there are no sales for vehicle class HDGV8b

           Calendar Year:  2008
                   Month:  July
                Altitude:  Low
     Minimum Temperature:  72.9 (F)
     Maximum Temperature:  90.2 (F)
       Absolute Humidity:  151. grains/lb
        Nominal Fuel RVP:   7.8 psi
           Weathered RVP:   7.5 psi
     Fuel Sulfur Content:   30. ppm

     Exhaust I/M Program:  No
        Evap I/M Program:  No
             ATP Program:  Yes
        Reformulated Gas:  No
```

Vehicle Type: GVWR:	LDGV	LDGT12 <6000	LDGT34 >6000	LDGT (All)	HDGV	LDDV	LDDT	HDDV	MC	All Veh
VMT Distribution:	0.7712	0.1620	0.0099		0.0120	0.0008	0.0002	0.0280	0.0160	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	0.849	0.877	0.522	0.856	0.876	0.363	0.470	0.389	2.50	0.864
Composite NOX :	0.570	0.664	0.640	0.662	2.951	0.726	0.654	6.963	0.99	0.800

```
* # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban local, 27.0
* File 1, Run 1, Scenario 12.
* # # # # # # # # # # # # # # # # # # # # # # # # #

* Reading Hourly Roadway VMT distribution from the following external
* data file: LOCALVMT.D
```

```
Reading User Supplied ROADWAY VMT Factors
M615 Comment:
            User supplied VMT mix.
M 48 Warning:
            there are no sales for vehicle class HDGV8b

                  Calendar Year:  2008
                          Month:  July
                       Altitude:  Low
            Minimum Temperature:  72.9 (F)
            Maximum Temperature:  90.2 (F)
              Absolute Humidity:  151. grains/lb
               Nominal Fuel RVP:   7.8 psi
                  Weathered RVP:   7.5 psi
            Fuel Sulfur Content:   30. ppm

            Exhaust I/M Program:  No
               Evap I/M Program:  No
                    ATP Program:  Yes
               Reformulated Gas:  No
```

Vehicle Type:	LDGV	LDGT12	LDGT34	LDGT	HDGV	LDDV	LDDT	HDDV	MC	All Veh
GVWR:		<6000	>6000	(All)						
VMT Distribution:	0.7961	0.1590	0.0039		0.0072	0.0009	0.0001	0.0178	0.0150	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	1.293	1.292	0.814	1.281	1.885	0.592	1.052	0.834	3.76	1.323
Composite NOX :	0.610	0.666	0.638	0.665	2.371	0.967	1.112	8.544	0.80	0.776

2011 PROJECTED ON-ROAD MOBILE EMISSIONS INVENTORY
ST. MARY PARISH
PEAK OZONE SEASON, RVP 7.8

ROAD CLASS	SPEED (MPH)	VOC (G/MI)	NOx (G/MI)	VMT (MI/DAY)	VOC (TPD)	NOx (TPD)
01	63.0	0.549	1.900	0	0.00	0.00
02	58.5	0.580	1.093	919,111	0.59	1.11
06	49.5	0.605	0.890	0	0.00	0.00
07	45.0	0.629	0.757	400,042	0.28	0.33
08	36.0	0.697	0.774	92,962	0.07	0.08
09	27.0	1.063	0.824	54,319	0.06	0.05
11	58.5	0.577	1.006	0	0.00	0.00
12	58.5	0.584	0.838	53,703	0.03	0.05
14	49.5	0.616	0.700	33,259	0.02	0.03
16	45.0	0.633	0.627	160,924	0.11	0.11
17	36.0	0.693	0.608	26,244	0.02	0.02
19	27.0	1.048	0.600	8,348	0.01	0.01
				1,748,912	1.20	1.78

ROADWAY FUNCTIONAL CLASS CODE

01 - RURAL PRINCIPAL ARTERIAL, INTERSTATE
02 - RURAL PRINCIPAL ARTERIAL, OTHER
06 - RURAL MINOR ARTERIAL
07 - RURAL MAJOR COLLECTOR
08 - RURAL MINOR COLLECTOR
09 - RURAL LOCAL ROAD

11 - URBAN PRINCIPAL ARTERIAL, INTERSTATE
12 - URBAN PRINCIPAL ARTERIAL, FREEWAY
14 - URBAN PRINCIPAL ARTERIAL, OTHER
16 - URBAN MINOR ARTERIAL
17 - URBAN COLLECTOR
19 - URBAN LOCAL ROAD

LDEQ, OEA, 3/31/2006

```
* St. Mary Parish; Ozone Season, 2011
******************  Header Section  ************************
MOBILE6 INPUT FILE :
POLLUTANTS         : HC NOX
RUN DATA
******************  Run Section  ***************************
>Year 2011 - St. Mary Parish Emission Factors, 7.8 RVP
NO REFUELING       :
MIN/MAX TEMP       : 72.9 90.2
ABSOLUTE HUMIDITY  : 150.5
FUEL RVP           : 7.8
REG DIST           : LA_REGD.D
ANTI-TAMP PROG     : 00 80 95 22222 21111111 1 11 072. 22222222
******************  Scenario Section  **********************
SCENARIO REC       : Rural interstate, 63.0
CALENDAR YEAR      : 2011
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 63.0 Non-Ramp 100.0 0.0 0.0 0.0
VMT FRACTIONS      :
0.599  0.038  0.127  0.014  0.007  0.068  0.007  0.005
0.004  0.015  0.017  0.019  0.069  0.003  0.002  0.006
******************  Scenario Section  **********************
SCENARIO REC       : Rural principal arterial, 58.5
CALENDAR YEAR      : 2011
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 58.5 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.652  0.048  0.160  0.016  0.008  0.036  0.004  0.003
0.002  0.008  0.009  0.010  0.037  0.002  0.001  0.004
******************  Scenario Section  **********************
SCENARIO REC       : Rural minor arterial, 49.5
CALENDAR YEAR      : 2011
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 49.5 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.672  0.046  0.155  0.017  0.008  0.032  0.003  0.002
0.002  0.007  0.008  0.009  0.032  0.002  0.001  0.004
******************  Scenario Section  **********************
SCENARIO REC       : Rural major collector, 45.0
CALENDAR YEAR      : 2011
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 45.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.667  0.054  0.178  0.017  0.008  0.023  0.002  0.002
0.001  0.005  0.006  0.007  0.024  0.001  0.001  0.004
******************  Scenario Section  **********************
SCENARIO REC       : Rural minor collector, 36.0
CALENDAR YEAR      : 2011
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 36.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.639  0.056  0.186  0.009  0.004  0.027  0.003  0.002
0.002  0.006  0.007  0.008  0.027  0.001  0.001  0.022
******************  Scenario Section  **********************
SCENARIO REC       : Rural local, 27.0
CALENDAR YEAR      : 2011
EVALUATION MONTH   : 7
ALTITUDE           : 1
VMT BY FACILITY    : localvmt.d
VMT FRACTIONS      :
0.654  0.057  0.189  0.003  0.002  0.024  0.002  0.002
0.001  0.005  0.006  0.007  0.025  0.001  0.001  0.021
******************  Scenario Section  **********************
SCENARIO REC       : Urban interstate, 58.5
CALENDAR YEAR      : 2011
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 58.5 Non-Ramp 100.0 0.0 0.0 0.0
VMT FRACTIONS      :
0.720  0.037  0.122  0.019  0.009  0.030  0.003  0.002
0.002  0.006  0.008  0.008  0.030  0.001  0.001  0.002
******************  Scenario Section  **********************
SCENARIO REC       : Urban other expressway, 58.5
CALENDAR YEAR      : 2011
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 58.5 Non-Ramp 100.0 0.0 0.0 0.0
VMT FRACTIONS      :
0.764  0.034  0.112  0.018  0.008  0.020  0.002  0.002
```

```
0.001  0.004  0.005  0.006  0.021  0.001  0.000  0.002
*******************  Scenario Section  ***********************
SCENARIO REC        : Urban principal arterial, 49.5
CALENDAR YEAR       : 2011
EVALUATION MONTH    : 7
ALTITUDE            : 1
AVERAGE SPEED       : 49.5 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS       :
0.766  0.034  0.113  0.018  0.008  0.018  0.002  0.001
0.001  0.004  0.005  0.005  0.018  0.001  0.000  0.006
*******************  Scenario Section  ***********************
SCENARIO REC        : Urban minor arterial, 45.0
CALENDAR YEAR       : 2011
EVALUATION MONTH    : 7
ALTITUDE            : 1
AVERAGE SPEED       : 45.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS       :
0.773  0.040  0.131  0.009  0.004  0.013  0.001  0.001
0.001  0.003  0.003  0.004  0.014  0.001  0.000  0.002
*******************  Scenario Section  ***********************
SCENARIO REC        : Urban collector, 36.0
CALENDAR YEAR       : 2011
EVALUATION MONTH    : 7
ALTITUDE            : 1
AVERAGE SPEED       : 36.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS       :
0.772  0.037  0.125  0.007  0.003  0.013  0.001  0.001
0.001  0.003  0.003  0.004  0.013  0.001  0.000  0.016
*******************  Scenario Section  ***********************
SCENARIO REC        : Urban local, 27.0
CALENDAR YEAR       : 2011
EVALUATION MONTH    : 7
ALTITUDE            : 1
VMT BY FACILITY     : localvmt.d
VMT FRACTIONS       :
0.797  0.037  0.122  0.003  0.001  0.008  0.001  0.001
0.000  0.002  0.002  0.002  0.009  0.000  0.000  0.015

END OF RUN
```

```
*****************************************************************************
* MOBILE6.2.03 (24-Sep-2003)                                                *
* Input file: C:\MOBILE6\RUN\110A1\LIMITED\78_RVP\2210 (file 1, run 1).     *
*****************************************************************************
*Year 2011 - St. Mary Parish Emission Factors, 7.8 RVP
  M603 Comment:
              User has disabled the calculation of REFUELING emissions.


* Reading Registration Distributions from the following external
* data file: LA_REGD.D

* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural interstate, 63.0
* File 1, Run 1, Scenario 1.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M581 Warning:
           The user supplied freeway average speed of 63.0
           will be used for all hours of the day. 100% of VMT
           has been assigned to the freeway roadway type for
           all hours of the day and all vehicle types.
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
            there are no sales for vehicle class HDGV8b

                  Calendar Year:  2011
                          Month:  July
                       Altitude:  Low
            Minimum Temperature:  72.9 (F)
            Maximum Temperature:  90.2 (F)
              Absolute Humidity:  151. grains/lb
               Nominal Fuel RVP:   7.8 psi
                  Weathered RVP:   7.5 psi
            Fuel Sulfur Content:   30. ppm

            Exhaust I/M Program:  No
               Evap I/M Program:  No
                    ATP Program:  Yes
               Reformulated Gas:  No
```

Vehicle Type: GVWR:	LDGV	LDGT12 <6000	LDGT34 >6000	LDGT (All)	HDGV	LDDV	LDDT	HDDV	MC	All Veh
VMT Distribution:	0.5985	0.1650	0.0207		0.0622	0.0005	0.0003	0.1468	0.0060	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	0.584	0.654	0.371	0.622	0.521	0.139	0.158	0.236	2.87	0.549
Composite NOX :	0.468	0.586	0.518	0.578	2.398	0.561	0.543	9.225	1.36	1.900

```
* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural principal arterial, 58.5
* File 1, Run 1, Scenario 2.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
           The user supplied arterial average speed of 58.5
           will be used for all hours of the day.  100% of VMT
           has been assigned to the arterial/collector roadway
           type for all hours of the day and all vehicle types.
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
            there are no sales for vehicle class HDGV8b
```

```
                Calendar Year:  2011
                        Month:  July
                     Altitude:  Low
          Minimum Temperature:  72.9 (F)
          Maximum Temperature:  90.2 (F)
            Absolute Humidity:  151. grains/lb
             Nominal Fuel RVP:   7.8 psi
                Weathered RVP:   7.5 psi
          Fuel Sulfur Content:   30. ppm

          Exhaust I/M Program:  No
             Evap I/M Program:  No
                  ATP Program:  Yes
             Reformulated Gas:  No
```

Vehicle Type: GVWR:	LDGV	LDGT12 <6000	LDGT34 >6000	LDGT (All)	HDGV	LDDV	LDDT	HDDV	MC	All Veh
VMT Distribution:	0.6514	0.2080	0.0236		0.0330	0.0006	0.0004	0.0790	0.0040	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	0.593	0.663	0.376	0.634	0.529	0.140	0.159	0.238	2.56	0.580
Composite NOX :	0.463	0.577	0.509	0.570	2.334	0.473	0.458	7.311	1.27	1.093

```
* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural minor arterial, 49.5
* File 1, Run 1, Scenario 3.
* # # # # # # # # # # # # # # # # # # # # # # # # #
 M583 Warning:
          The user supplied arterial average speed of 49.5
          will be used for all hours of the day.  100% of VMT
          has been assigned to the arterial/collector roadway
          type for all hours of the day and all vehicle types.
 M615 Comment:
             User supplied VMT mix.
 M 48 Warning:
           there are no sales for vehicle class HDGV8b

                Calendar Year:  2011
                        Month:  July
                     Altitude:  Low
          Minimum Temperature:  72.9 (F)
          Maximum Temperature:  90.2 (F)
            Absolute Humidity:  151. grains/lb
             Nominal Fuel RVP:   7.8 psi
                Weathered RVP:   7.5 psi
          Fuel Sulfur Content:   30. ppm

          Exhaust I/M Program:  No
             Evap I/M Program:  No
                  ATP Program:  Yes
             Reformulated Gas:  No
```

Vehicle Type: GVWR:	LDGV	LDGT12 <6000	LDGT34 >6000	LDGT (All)	HDGV	LDDV	LDDT	HDDV	MC	All Veh
VMT Distribution:	0.6714	0.2010	0.0246		0.0292	0.0006	0.0004	0.0688	0.0040	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	0.617	0.687	0.389	0.654	0.559	0.145	0.166	0.255	2.31	0.605
Composite NOX :	0.453	0.560	0.491	0.552	2.200	0.367	0.353	5.706	1.08	0.890

```
* # # # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural major collector, 45.0
* File 1, Run 1, Scenario 4.
* # # # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 45.0
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
             User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b

                   Calendar Year:  2011
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No
```

Vehicle Type: GVWR:	LDGV	LDGT12 <6000	LDGT34 >6000	LDGT (All)	HDGV	LDDV	LDDT	HDDV	MC	All Veh
VMT Distribution:	0.6664	0.2320	0.0246		0.0208	0.0006	0.0004	0.0512	0.0040	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	0.633	0.700	0.397	0.671	0.580	0.150	0.173	0.270	2.33	0.629
Composite NOX :	0.448	0.551	0.484	0.545	2.118	0.337	0.325	5.268	1.02	0.757

```
* # # # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural minor collector, 36.0
* File 1, Run 1, Scenario 5.
* # # # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 36.0
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
             User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b

                   Calendar Year:  2011
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm
```

```
              Exhaust I/M Program:  No
                 Evap I/M Program:  No
                      ATP Program:  Yes
                 Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34     LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.6384    0.2420    0.0128              0.0249    0.0006    0.0002    0.0591    0.0220    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      0.667     0.728     0.414     0.712     0.652     0.166     0.200     0.318      2.46     0.697
    Composite NOX :      0.443     0.538     0.470     0.534     1.987     0.312     0.305     4.796      0.99     0.774
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural local, 27.0
* File 1, Run 1, Scenario 6.
* # # # # # # # # # # # # # # # # # # # # # # # # #

* Reading Hourly Roadway VMT distribution from the following external
* data file: LOCALVMT.D

  Reading User Supplied ROADWAY VMT Factors
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b

                   Calendar Year:  2011
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34     LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.6534    0.2460    0.0049              0.0216    0.0006    0.0001    0.0524    0.0210    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      1.005     1.054     0.651     1.046     1.328     0.281     0.382     0.698      3.72     1.063
    Composite NOX :      0.481     0.545     0.493     0.544     1.625     0.417     0.431     6.130      0.80     0.824
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban interstate, 58.5
* File 1, Run 1, Scenario 7.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M581 Warning:
            The user supplied freeway average speed of 58.5
            will be used for all hours of the day. 100% of VMT
            has been assigned to the freeway roadway type for
            all hours of the day and all vehicle types.
  M615 Comment:
```

```
              User supplied VMT mix.
 M 48 Warning:
             there are no sales for vehicle class HDGV8b

                   Calendar Year:  2011
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:                <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.7194    0.1590    0.0276              0.0273    0.0006    0.0004    0.0637    0.0020    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
     Composite VOC :      0.593     0.663     0.376     0.621     0.526     0.140     0.158     0.237      2.56     0.577
     Composite NOX :      0.463     0.576     0.507     0.566     2.323     0.473     0.455     7.867      1.27     1.006
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban other expressway, 58.5
* File 1, Run 1, Scenario 8.
* # # # # # # # # # # # # # # # # # # # # # # # # # #
  M581 Warning:
            The user supplied freeway average speed of 58.5
            will be used for all hours of the day. 100% of VMT
            has been assigned to the freeway roadway type for
            all hours of the day and all vehicle types.
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b

                   Calendar Year:  2011
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:                <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.7633    0.1460    0.0256              0.0181    0.0007    0.0004    0.0439    0.0020    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
```

```
    Composite VOC :      0.593     0.663     0.375     0.620     0.527     0.140     0.158     0.239      2.56     0.584
    Composite NOX :      0.463     0.576     0.505     0.566     2.328     0.473     0.455     7.817      1.27     0.838
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban principal arterial, 49.5
* File 1, Run 1, Scenario 9.
* # # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 49.5
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
             User supplied VMT mix.
  M 48 Warning:
            there are no sales for vehicle class HDGV8b

                  Calendar Year:  2011
                          Month:  July
                       Altitude:  Low
            Minimum Temperature:  72.9 (F)
            Maximum Temperature:  90.2 (F)
              Absolute Humidity:  151. grains/lb
               Nominal Fuel RVP:   7.8 psi
                  Weathered RVP:   7.5 psi
            Fuel Sulfur Content:   30. ppm

            Exhaust I/M Program:  No
               Evap I/M Program:  No
                    ATP Program:  Yes
               Reformulated Gas:  No

       Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:                <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
   VMT Distribution:    0.7653    0.1470    0.0256              0.0165    0.0007    0.0004    0.0385    0.0060    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      0.617     0.686     0.388     0.642     0.556     0.145     0.164     0.255      2.31     0.616
    Composite NOX :      0.453     0.559     0.489     0.549     2.196     0.367     0.352     5.599      1.08     0.700
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban minor arterial, 45.0
* File 1, Run 1, Scenario 10.
* # # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 45.0
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
             User supplied VMT mix.
  M 48 Warning:
            there are no sales for vehicle class HDGV8b

                  Calendar Year:  2011
                          Month:  July
                       Altitude:  Low
            Minimum Temperature:  72.9 (F)
            Maximum Temperature:  90.2 (F)
              Absolute Humidity:  151. grains/lb
               Nominal Fuel RVP:   7.8 psi
```

```
                Weathered RVP:   7.5 psi
            Fuel Sulfur Content:   30. ppm

            Exhaust I/M Program:  No
               Evap I/M Program:  No
                    ATP Program:  Yes
               Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
             GVWR:                <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.7723    0.1710    0.0128              0.0119    0.0007    0.0002    0.0291    0.0020    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      0.633     0.700     0.396     0.678     0.589     0.150     0.175     0.274      2.33     0.633
    Composite NOX :      0.448     0.551     0.482     0.546     2.143     0.337     0.327     5.231      1.02     0.627
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban collector, 36.0
* File 1, Run 1, Scenario 11.
* # # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
           The user supplied arterial average speed of 36.0
           will be used for all hours of the day.  100% of VMT
           has been assigned to the arterial/collector roadway
           type for all hours of the day and all vehicle types.
  M615 Comment:
            User supplied VMT mix.
  M 48 Warning:
           there are no sales for vehicle class HDGV8b

                 Calendar Year:  2011
                         Month:  July
                      Altitude:  Low
            Minimum Temperature:  72.9 (F)
            Maximum Temperature:  90.2 (F)
              Absolute Humidity:  151. grains/lb
               Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
            Fuel Sulfur Content:   30. ppm

            Exhaust I/M Program:  No
               Evap I/M Program:  No
                    ATP Program:  Yes
               Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
             GVWR:                <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.7713    0.1620    0.0099              0.0119    0.0007    0.0001    0.0281    0.0160    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      0.667     0.728     0.413     0.710     0.659     0.166     0.199     0.324      2.46     0.693
    Composite NOX :      0.443     0.538     0.469     0.534     2.006     0.312     0.304     4.794      0.99     0.608
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban local, 27.0
* File 1, Run 1, Scenario 12.
* # # # # # # # # # # # # # # # # # # # # # # # # # #

* Reading Hourly Roadway VMT distribution from the following external
* data file: LOCALVMT.D
```

```
Reading User Supplied ROADWAY VMT Factors
M615 Comment:
            User supplied VMT mix.
M 48 Warning:
           there are no sales for vehicle class HDGV8b

                 Calendar Year:  2011
                         Month:  July
                      Altitude:  Low
           Minimum Temperature:  72.9 (F)
           Maximum Temperature:  90.2 (F)
             Absolute Humidity:  151. grains/lb
              Nominal Fuel RVP:   7.8 psi
                 Weathered RVP:   7.5 psi
           Fuel Sulfur Content:   30. ppm

           Exhaust I/M Program:  No
              Evap I/M Program:  No
                   ATP Program:  Yes
              Reformulated Gas:  No
```

Vehicle Type: GVWR:	LDGV	LDGT12 <6000	LDGT34 >6000	LDGT (All)	HDGV	LDDV	LDDT	HDDV	MC	All Veh
VMT Distribution:	0.7963	0.1590	0.0039		0.0072	0.0007	0.0001	0.0178	0.0150	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	1.005	1.054	0.643	1.044	1.313	0.281	0.374	0.692	3.72	1.048
Composite NOX :	0.481	0.545	0.467	0.543	1.606	0.417	0.424	5.902	0.80	0.600

2014 PROJECTED ON-ROAD MOBILE EMISSIONS INVENTORY
ST. MARY PARISH
PEAK OZONE SEASON, RVP 7.8

ROAD CLASS	SPEED (MPH)	VOC (G/MI)	NOx (G/MI)	VMT (MI/DAY)	VOC (TPD)	NOx (TPD)
01	63.0	0.441	1.270	0	0.00	0.00
02	58.5	0.462	0.764	968,206	0.49	0.82
06	49.5	0.481	0.634	0	0.00	0.00
07	45.0	0.499	0.550	421,410	0.23	0.26
08	36.0	0.562	0.565	97,927	0.06	0.06
09	27.0	0.856	0.605	54,538	0.05	0.04
11	58.5	0.458	0.706	0	0.00	0.00
12	58.5	0.463	0.601	55,781	0.03	0.04
14	49.5	0.489	0.513	34,547	0.02	0.02
16	45.0	0.500	0.467	166,359	0.09	0.09
17	36.0	0.553	0.458	26,527	0.02	0.01
19	27.0	0.837	0.461	8,390	0.01	0.00
				1,833,685	1.00	1.33

ROADWAY FUNCTIONAL CLASS CODE

01 - RURAL PRINCIPAL ARTERIAL, INTERSTATE
02 - RURAL PRINCIPAL ARTERIAL, OTHER
06 - RURAL MINOR ARTERIAL
07 - RURAL MAJOR COLLECTOR
08 - RURAL MINOR COLLECTOR
09 - RURAL LOCAL ROAD

11 - URBAN PRINCIPAL ARTERIAL, INTERSTATE
12 - URBAN PRINCIPAL ARTERIAL, FREEWAY
14 - URBAN PRINCIPAL ARTERIAL, OTHER
16 - URBAN MINOR ARTERIAL
17 - URBAN COLLECTOR
19 - URBAN LOCAL ROAD

LDEQ, OEA, 3/31/2006

```
* St. Mary Parish; Ozone Season, 2014
******************  Header Section  ************************
MOBILE6 INPUT FILE :
POLLUTANTS         : HC NOX
RUN DATA
******************  Run Section  ***************************
>Year 2014 - St. Mary Parish Emission Factors
NO REFUELING       :
MIN/MAX TEMP       : 72.9 90.2
ABSOLUTE HUMIDITY  : 150.5
FUEL RVP           : 7.8
REG DIST           : LA_REGD.D
ANTI-TAMP PROG     : 00 80 95 22222 21111111 1 11 072. 22222222
******************  Scenario Section  ***********************
SCENARIO REC       : Rural interstate, 63.0
CALENDAR YEAR      : 2014
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 63.0 Non-Ramp 100.0 0.0 0.0 0.0
VMT FRACTIONS      :
0.599  0.038  0.127  0.014  0.007  0.068  0.007  0.005
0.004  0.015  0.017  0.019  0.069  0.003  0.002  0.006
******************  Scenario Section  ***********************
SCENARIO REC       : Rural principal arterial, 58.5
CALENDAR YEAR      : 2014
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 58.5 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.652  0.048  0.160  0.016  0.008  0.036  0.004  0.003
0.002  0.008  0.009  0.010  0.037  0.002  0.001  0.004
******************  Scenario Section  ***********************
SCENARIO REC       : Rural minor arterial, 49.5
CALENDAR YEAR      : 2014
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 49.5 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.672  0.046  0.155  0.017  0.008  0.032  0.003  0.002
0.002  0.007  0.008  0.009  0.032  0.002  0.001  0.004
******************  Scenario Section  ***********************
SCENARIO REC       : Rural major collector, 45.0
CALENDAR YEAR      : 2014
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 45.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.667  0.054  0.178  0.017  0.008  0.023  0.002  0.002
0.001  0.005  0.006  0.007  0.024  0.001  0.001  0.004
******************  Scenario Section  ***********************
SCENARIO REC       : Rural minor collector, 36.0
CALENDAR YEAR      : 2014
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 36.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS      :
0.639  0.056  0.186  0.009  0.004  0.027  0.003  0.002
0.002  0.006  0.007  0.008  0.027  0.001  0.001  0.022
******************  Scenario Section  ***********************
SCENARIO REC       : Rural local, 27.0
CALENDAR YEAR      : 2014
EVALUATION MONTH   : 7
ALTITUDE           : 1
VMT BY FACILITY    : localvmt.d
VMT FRACTIONS      :
0.654  0.057  0.189  0.003  0.002  0.024  0.002  0.002
0.001  0.005  0.006  0.007  0.025  0.001  0.001  0.021
******************  Scenario Section  ***********************
SCENARIO REC       : Urban interstate, 58.5
CALENDAR YEAR      : 2014
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 58.5 Non-Ramp 100.0 0.0 0.0 0.0
VMT FRACTIONS      :
0.720  0.037  0.122  0.019  0.009  0.030  0.003  0.002
0.002  0.006  0.008  0.008  0.030  0.001  0.001  0.002
******************  Scenario Section  ***********************
SCENARIO REC       : Urban other expressway, 58.5
CALENDAR YEAR      : 2014
EVALUATION MONTH   : 7
ALTITUDE           : 1
AVERAGE SPEED      : 58.5 Non-Ramp 100.0 0.0 0.0 0.0
VMT FRACTIONS      :
0.764  0.034  0.112  0.018  0.008  0.020  0.002  0.002
```

```
0.001  0.004  0.005  0.006  0.021  0.001  0.000  0.002
******************  Scenario Section  **********************
SCENARIO REC        : Urban principal arterial, 49.5
CALENDAR YEAR       : 2014
EVALUATION MONTH    : 7
ALTITUDE            : 1
AVERAGE SPEED       : 49.5 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS       :
0.766  0.034  0.113  0.018  0.008  0.018  0.002  0.001
0.001  0.004  0.005  0.005  0.018  0.001  0.000  0.006
******************  Scenario Section  **********************
SCENARIO REC        : Urban minor arterial, 45.0
CALENDAR YEAR       : 2014
EVALUATION MONTH    : 7
ALTITUDE            : 1
AVERAGE SPEED       : 45.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS       :
0.773  0.040  0.131  0.009  0.004  0.013  0.001  0.001
0.001  0.003  0.003  0.004  0.014  0.001  0.000  0.002
******************  Scenario Section  **********************
SCENARIO REC        : Urban collector, 36.0
CALENDAR YEAR       : 2014
EVALUATION MONTH    : 7
ALTITUDE            : 1
AVERAGE SPEED       : 36.0 Arterial 0.0 100.0 0.0 0.0
VMT FRACTIONS       :
0.772  0.037  0.125  0.007  0.003  0.013  0.001  0.001
0.001  0.003  0.003  0.004  0.013  0.001  0.000  0.016
******************  Scenario Section  **********************
SCENARIO REC        : Urban local, 27.0
CALENDAR YEAR       : 2014
EVALUATION MONTH    : 7
ALTITUDE            : 1
VMT BY FACILITY     : localvmt.d
VMT FRACTIONS       :
0.797  0.037  0.122  0.003  0.001  0.008  0.001  0.001
0.000  0.002  0.002  0.002  0.009  0.000  0.000  0.015

END OF RUN
```

```
*************************************************************************
* MOBILE6.2.03 (24-Sep-2003)                                            *
* Input file: C:\MOBILE6\RUN\110A1\LIMITED\22101_14.IN (file 1, run 1).  *
*************************************************************************
*Year 2014 - St. Mary Parish Emission Factors
  M603 Comment:
              User has disabled the calculation of REFUELING emissions.


* Reading Registration Distributions from the following external
* data file: LA_REGD.D

* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural interstate, 63.0
* File 1, Run 1, Scenario 1.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M581 Warning:
            The user supplied freeway average speed of 63.0
            will be used for all hours of the day. 100% of VMT
            has been assigned to the freeway roadway type for
            all hours of the day and all vehicle types.
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b
  M 48 Warning:
             there are no sales for vehicle class LDDT12

                  Calendar Year:  2014
                          Month:  July
                       Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No
```

Vehicle Type: GVWR:	LDGV	LDGT12 <6000	LDGT34 >6000	LDGT (All)	HDGV	LDDV	LDDT	HDDV	MC	All Veh
VMT Distribution:	0.5985	0.1650	0.0207		0.0620	0.0005	0.0003	0.1470	0.0060	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	0.459	0.532	0.304	0.507	0.406	0.086	0.114	0.200	2.87	0.441
Composite NOX :	0.363	0.475	0.403	0.467	1.518	0.297	0.357	5.874	1.36	1.270

```
* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural principal arterial, 58.5
* File 1, Run 1, Scenario 2.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 58.5
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
              User supplied VMT mix.
```

```
M 48 Warning:
            there are no sales for vehicle class HDGV8b
M 48 Warning:
            there are no sales for vehicle class LDDT12

                  Calendar Year:  2014
                          Month:  July
                       Altitude:  Low
            Minimum Temperature:  72.9 (F)
            Maximum Temperature:  90.2 (F)
              Absolute Humidity:  151. grains/lb
               Nominal Fuel RVP:   7.8 psi
                  Weathered RVP:   7.5 psi
            Fuel Sulfur Content:   30. ppm

            Exhaust I/M Program:  No
               Evap I/M Program:  No
                    ATP Program:  Yes
               Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
             GVWR:                <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.6514    0.2080    0.0236              0.0329    0.0006    0.0004    0.0791    0.0040    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      0.465     0.539     0.308     0.515     0.411     0.086     0.115     0.202      2.56     0.462
    Composite NOX :      0.360     0.468     0.397     0.461     1.477     0.250     0.301     4.664      1.27     0.764
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural minor arterial, 49.5
* File 1, Run 1, Scenario 3.
* # # # # # # # # # # # # # # # # # # # # # # # # # # #
M583 Warning:
           The user supplied arterial average speed of 49.5
           will be used for all hours of the day.  100% of VMT
           has been assigned to the arterial/collector roadway
           type for all hours of the day and all vehicle types.
M615 Comment:
             User supplied VMT mix.
M 48 Warning:
            there are no sales for vehicle class HDGV8b
M 48 Warning:
            there are no sales for vehicle class LDDT12

                  Calendar Year:  2014
                          Month:  July
                       Altitude:  Low
            Minimum Temperature:  72.9 (F)
            Maximum Temperature:  90.2 (F)
              Absolute Humidity:  151. grains/lb
               Nominal Fuel RVP:   7.8 psi
                  Weathered RVP:   7.5 psi
            Fuel Sulfur Content:   30. ppm

            Exhaust I/M Program:  No
               Evap I/M Program:  No
                    ATP Program:  Yes
               Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
             GVWR:                <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
```

```
  VMT Distribution:     0.6714    0.2010    0.0246              0.0291    0.0006    0.0004    0.0689    0.0040    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
     Composite VOC :       0.483     0.555     0.317     0.529     0.434     0.090     0.119     0.217      2.31     0.481
     Composite NOX :       0.352     0.454     0.382     0.447     1.391     0.194     0.233     3.647      1.08     0.634
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural major collector, 45.0
* File 1, Run 1, Scenario 4.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 45.0
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
             User supplied VMT mix.
  M 48 Warning:
            there are no sales for vehicle class HDGV8b
  M 48 Warning:
            there are no sales for vehicle class LDDT12

                  Calendar Year:  2014
                          Month:  July
                       Altitude:  Low
            Minimum Temperature:  72.9 (F)
            Maximum Temperature:  90.2 (F)
              Absolute Humidity:  151. grains/lb
               Nominal Fuel RVP:   7.8 psi
                  Weathered RVP:   7.5 psi
            Fuel Sulfur Content:   30. ppm

            Exhaust I/M Program:  No
               Evap I/M Program:  No
                    ATP Program:  Yes
               Reformulated Gas:  No

       Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:                <6000     >6000     (All)
                         ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.6664    0.2320    0.0246              0.0207    0.0006    0.0004    0.0513    0.0040    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
     Composite VOC :       0.494     0.565     0.323     0.542     0.450     0.093     0.124     0.229      2.33     0.499
     Composite NOX :       0.349     0.448     0.376     0.441     1.341     0.178     0.213     3.360      1.02     0.550
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural minor collector, 36.0
* File 1, Run 1, Scenario 5.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 36.0
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
             User supplied VMT mix.
  M 48 Warning:
            there are no sales for vehicle class HDGV8b
  M 48 Warning:
            there are no sales for vehicle class LDDT12
```

```
                Calendar Year:  2014
                        Month:  July
                     Altitude:  Low
          Minimum Temperature:  72.9 (F)
          Maximum Temperature:  90.2 (F)
            Absolute Humidity:  151. grains/lb
             Nominal Fuel RVP:   7.8 psi
                Weathered RVP:   7.5 psi
          Fuel Sulfur Content:   30. ppm

          Exhaust I/M Program:  No
             Evap I/M Program:  No
                 ATP Program:  Yes
             Reformulated Gas:  No

     Vehicle Type:      LDGV    LDGT12    LDGT34     LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
             GVWR:               <6000     >6000     (All)
                       ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:    0.6384    0.2420    0.0128              0.0249    0.0006    0.0002    0.0591    0.0220    1.0000
 ---------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      0.521     0.586     0.337     0.573     0.507     0.103     0.140     0.270      2.46     0.562
    Composite NOX :      0.345     0.437     0.365     0.433     1.258     0.165     0.197     3.056      0.99     0.565
 ---------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Rural local, 27.0
* File 1, Run 1, Scenario 6.
* # # # # # # # # # # # # # # # # # # # # # # # # # #

* Reading Hourly Roadway VMT distribution from the following external
* data file: LOCALVMT.D

  Reading User Supplied ROADWAY VMT Factors
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b
  M 48 Warning:
             there are no sales for vehicle class LDDT12

                Calendar Year:  2014
                        Month:  July
                     Altitude:  Low
          Minimum Temperature:  72.9 (F)
          Maximum Temperature:  90.2 (F)
            Absolute Humidity:  151. grains/lb
             Nominal Fuel RVP:   7.8 psi
                Weathered RVP:   7.5 psi
          Fuel Sulfur Content:   30. ppm

          Exhaust I/M Program:  No
             Evap I/M Program:  No
                 ATP Program:  Yes
             Reformulated Gas:  No

     Vehicle Type:      LDGV    LDGT12    LDGT34     LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
             GVWR:               <6000     >6000     (All)
                       ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:    0.6534    0.2460    0.0049              0.0215    0.0006    0.0001    0.0525    0.0210    1.0000
 ---------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      0.787     0.845     0.534     0.839     1.029     0.177     0.252     0.593      3.72     0.856
    Composite NOX :      0.381     0.446     0.381     0.445     1.029     0.220     0.264     3.902      0.80     0.605
```

```
* # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban interstate, 58.5
* File 1, Run 1, Scenario 7.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M581 Warning:
            The user supplied freeway average speed of 58.5
            will be used for all hours of the day. 100% of VMT
            has been assigned to the freeway roadway type for
            all hours of the day and all vehicle types.
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b
  M 48 Warning:
             there are no sales for vehicle class LDDT12

                   Calendar Year:  2014
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No

       Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:                <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.7194    0.1590    0.0276              0.0273    0.0006    0.0004    0.0637    0.0020    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
     Composite VOC :      0.465     0.539     0.308     0.504     0.410     0.086     0.115     0.201      2.56     0.458
     Composite NOX :      0.360     0.468     0.395     0.457     1.472     0.250     0.301     5.006      1.27     0.706
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban other expressway, 58.5
* File 1, Run 1, Scenario 8.
* # # # # # # # # # # # # # # # # # # # # # # # # #
  M581 Warning:
            The user supplied freeway average speed of 58.5
            will be used for all hours of the day. 100% of VMT
            has been assigned to the freeway roadway type for
            all hours of the day and all vehicle types.
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b
  M 48 Warning:
             there are no sales for vehicle class LDDT12

                   Calendar Year:  2014
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
```

```
              Absolute Humidity:  151. grains/lb
               Nominal Fuel RVP:   7.8 psi
                  Weathered RVP:   7.5 psi
            Fuel Sulfur Content:   30. ppm

            Exhaust I/M Program:  No
               Evap I/M Program:  No
                    ATP Program:  Yes
               Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.7633    0.1460    0.0256              0.0181    0.0007    0.0004    0.0439    0.0020    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      0.465     0.539     0.307     0.504     0.409     0.086     0.115     0.203      2.56     0.463
    Composite NOX :      0.360     0.468     0.393     0.457     1.473     0.250     0.301     4.973      1.27     0.601
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban principal arterial, 49.5
* File 1, Run 1, Scenario 9.
* # # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
           The user supplied arterial average speed of 49.5
           will be used for all hours of the day.  100% of VMT
           has been assigned to the arterial/collector roadway
           type for all hours of the day and all vehicle types.
  M615 Comment:
            User supplied VMT mix.
  M 48 Warning:
           there are no sales for vehicle class HDGV8b
  M 48 Warning:
           there are no sales for vehicle class LDDT12

                 Calendar Year:  2014
                         Month:  July
                      Altitude:  Low
           Minimum Temperature:  72.9 (F)
           Maximum Temperature:  90.2 (F)
              Absolute Humidity:  151. grains/lb
               Nominal Fuel RVP:   7.8 psi
                  Weathered RVP:   7.5 psi
            Fuel Sulfur Content:   30. ppm

            Exhaust I/M Program:  No
               Evap I/M Program:  No
                    ATP Program:  Yes
               Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.7653    0.1470    0.0256              0.0165    0.0007    0.0004    0.0385    0.0060    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      0.483     0.555     0.317     0.520     0.433     0.090     0.119     0.216      2.31     0.489
    Composite NOX :      0.352     0.454     0.381     0.443     1.390     0.194     0.233     3.565      1.08     0.513
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban minor arterial, 45.0
* File 1, Run 1, Scenario 10.
```

```
* # # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 45.0
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b
  M 48 Warning:
             there are no sales for vehicle class LDDT12

                   Calendar Year:  2014
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No
```

Vehicle Type: GVWR:	LDGV	LDGT12 <6000	LDGT34 >6000	LDGT (All)	HDGV	LDDV	LDDT	HDDV	MC	All Veh
VMT Distribution:	0.7723	0.1710	0.0128		0.0119	0.0007	0.0002	0.0291	0.0020	1.0000
Composite Emission Factors (g/mi):										
Composite VOC :	0.494	0.565	0.323	0.548	0.457	0.093	0.124	0.233	2.33	0.500
Composite NOX :	0.349	0.447	0.375	0.442	1.353	0.178	0.213	3.344	1.02	0.467

```
* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban collector, 36.0
* File 1, Run 1, Scenario 11.
* # # # # # # # # # # # # # # # # # # # # # # # # # #
  M583 Warning:
            The user supplied arterial average speed of 36.0
            will be used for all hours of the day.  100% of VMT
            has been assigned to the arterial/collector roadway
            type for all hours of the day and all vehicle types.
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b
  M 48 Warning:
             there are no sales for vehicle class LDDT12

                   Calendar Year:  2014
                           Month:  July
                        Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm
```

```
            Exhaust I/M Program:  No
               Evap I/M Program:  No
                    ATP Program:  Yes
               Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.7713    0.1620    0.0099              0.0119    0.0007    0.0001    0.0281    0.0160    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      0.521     0.586     0.337     0.572     0.511     0.103     0.140     0.275      2.46     0.553
    Composite NOX :      0.345     0.437     0.364     0.433     1.266     0.165     0.197     3.066      0.99     0.458
 ---------------------------------------------------------------------------------------------------------------------------

* # # # # # # # # # # # # # # # # # # # # # # # # # #
* Urban local, 27.0
* File 1, Run 1, Scenario 12.
* # # # # # # # # # # # # # # # # # # # # # # # # # #

* Reading Hourly Roadway VMT distribution from the following external
* data file: LOCALVMT.D

  Reading User Supplied ROADWAY VMT Factors
  M615 Comment:
              User supplied VMT mix.
  M 48 Warning:
             there are no sales for vehicle class HDGV8b
  M 48 Warning:
             there are no sales for vehicle class LDDT12

                   Calendar Year:  2014
                          Month:  July
                       Altitude:  Low
             Minimum Temperature:  72.9 (F)
             Maximum Temperature:  90.2 (F)
               Absolute Humidity:  151. grains/lb
                Nominal Fuel RVP:   7.8 psi
                   Weathered RVP:   7.5 psi
             Fuel Sulfur Content:   30. ppm

             Exhaust I/M Program:  No
                Evap I/M Program:  No
                     ATP Program:  Yes
                Reformulated Gas:  No

      Vehicle Type:      LDGV    LDGT12    LDGT34      LDGT      HDGV      LDDV      LDDT      HDDV        MC   All Veh
              GVWR:               <6000     >6000     (All)
                        ------    ------    ------    ------    ------    ------    ------    ------    ------    ------
  VMT Distribution:     0.7963    0.1590    0.0039              0.0072    0.0007    0.0001    0.0178    0.0150    1.0000
 ---------------------------------------------------------------------------------------------------------------------------
 Composite Emission Factors (g/mi):
    Composite VOC :      0.787     0.845     0.528     0.838     1.020     0.177     0.252     0.586      3.72     0.837
    Composite NOX :      0.381     0.446     0.362     0.444     1.020     0.220     0.264     3.719      0.80     0.461
 ---------------------------------------------------------------------------------------------------------------------------
```