

6.B Sector B. Paper and Allied Products Manufacturing

6.B.1 Covered Storm Water Discharges

The requirements in Part 6.B apply to storm water discharges associated with industrial activity from Paper and Allied Products Manufacturing facilities as identified by the SIC Codes specified under Sector B in Table 1 of Part 1. You must comply with the Part 6 sector-specific requirements associated with your primary industrial activity and any co-located industrial activities as defined in Part 12. The sector-specific requirements apply to those areas of your facility where those sector-specific activities occur.

6.B.2 Industrial Activities Covered by Sector B

SIC Codes covered under Sector B are:

2611, 2621, 2631, 2652-2657, and 2671-2679

The types of activities that permittees under Sector B are primarily engaged in are:

- 6.B.2.1 manufacture of pulps from wood and other cellulose fibers and from rags;
- 6.B.2.2 manufacture of paper and paperboard into converted products, i.e. paper coated off the paper machine, paper bags, paper boxes and envelopes; and
- 6.B.2.3 manufacture of bags of plastic film and sheet.

6.B.3 Monitoring and Reporting Requirements (See also Part 5)

Table B-1. SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK MONITORING			
Part of Permit Affected/Supplemental Requirements			
<i>Note: In addition to the following requirements, you must also comply with the requirements listed in Part 5 of the MSGP. If your SIC Code is not listed below then numeric limitations and benchmark monitoring do not apply except as otherwise noted below.</i>			
Subsector (You may be subject to requirements for more than one sector/subsector.)	Parameter	Benchmark Monitoring Concentration¹	Numeric Limitation²
COD monitoring is only applicable to SIC Code 2631 (Paperboard Mills)	Chemical Oxygen Demand (COD)	120 mg/L	---
	Total Organic Carbon (TOC)	---	50 mg/L
	Oil & Grease	---	15 mg/L

¹ Monitor once/quarter for the year 2 and year 4 monitoring years (See Part 5.4.2 for possible year 4 monitoring waiver).

² The discharge from this permitted outfall shall not exceed a Daily Maximum of 50 mg/L Total Organic Carbon (TOC) or 15 mg/L Oil and Grease. **Unless required by Part 5.10 of this permit, analytical sampling and analysis of these parameters on a regular basis are not required.**