Department of Environmental Quality

LOUISIANA

P.O. Box 4314 Baton Rouge, LA 70821 Attn: Stage II Program

Notice of Decommissioning Stage II Vapor Recovery Completion



Instructions: Complete this form and mail to the address listed above, **no later than 10 calendar days** after completion of all decommissioning activity.

According to LAC 33:III.2132, all gasoline-dispensing facilities have no later than 18 months from July 6, 2020 to either remove or decommission Stage II vapor recovery equipment at the facility.

Facility and Contractor Information

Agency Interest No.: Facility ID No.: # of Pumps affected: Facility's Legal Name:	Gasoline Dispensing Facility Information							
Facility's Local Name: Facility Address: Facility Address: Name: Email Address: Telephone No.: Mailing Address: Stage II Decommissioning Activity Checklist Relieve pressure in the tank ullage by removing all pressure/vacuum vent valves. Drain all liquid collection points and vapor pumps for individual dispensers. Remove all centrally located vapor pumps; Disconnect all electrical components of the Stage II system so that no electrical hazards are created. e.g., all vapor pumping or processing units and dispenser electronics Reprogram the dispenser electronics to reflect that Stage II vapor recovery is no longer in service. Securely seal the below-grade vapor piping at a height below the level of the base of the dispenser using only threaded plugs, threaded caps, or glued fittings. Disconnect and seal off the vapor piping inside the dispenser cabinet using only threaded plugs, threaded caps, or glue fittings. Securely seal the lower end of the vapor piping inside the dispenser cabinet using only threaded plugs, threaded caps, or glue fittings. Replace the stage II hanging hardware including hoses, nozzles, swivels, and breakaway components ich conduct a visual check to verify that the visible components of the storage system are left in a condition that will reliably prevent the release of any vapors or liquids from any component of the storage system anasociated with Stage II vapor recovery.	Agency Interest No.:							
Facility's Local Name: Facility Address: Facility Address: Name: Email Address: Telephone No.: Mailing Address: Stage II Decommissioning Activity Checklist Relieve pressure in the tank ullage by removing all pressure/vacuum vent valves. Drain all liquid collection points and vapor pumps for individual dispensers. Remove all centrally located vapor pumps; Disconnect all electrical components of the Stage II system so that no electrical hazards are created. e.g., all vapor pumping or processing units and dispenser electronics Reprogram the dispenser electronics to reflect that Stage II vapor recovery is no longer in service. Securely seal the below-grade vapor piping at a height below the level of the base of the dispenser using only threaded plugs, threaded caps, or glued fittings. Disconnect and seal off the vapor piping inside the dispenser cabinet using only threaded plugs, threaded caps, or glue fittings. Securely seal the lower end of the vapor piping inside the dispenser cabinet using only threaded plugs, threaded caps, or glue fittings. Replace the stage II hanging hardware including hoses, nozzles, swivels, and breakaway components ich conduct a visual check to verify that the visible components of the storage system are left in a condition that will reliably prevent the release of any vapors or liquids from any component of the storage system anasociated with Stage II vapor recovery.								
Facility Address: Owner/Operator Information (Facility Contact) Name: Email Address: Telephone No.: Mailing Address: Stage II Decommissioning Activity Checklist Y N N Relieve pressure in the tank ullage by removing all pressure/vacuum vent valves. Image: Completed? Y N N Drain all liquid collection points and vapor pumps for individual dispensers. Image: Completed? Y N N Beinove all centrally located vapor pumps; Image: Completed? Y N N Disconnect all electrical components of the Stage II system so that no electrical hazards are created. Image: Completed? Image: Completed? Securely seal the below-grade vapor piping at a height below the level of the base of the dispenser Image: Completed? Image: Completed? Securely seal the below-grade vapor oping at a height below the level of the base of the dispenser Image: Completed? Image: Completed? Securely seal the below-erade vapor piping at the tank top if this can be done without excavation and without interfering with the vent line using only threaded plugs, threaded caps, or glue fittings. Image: Completed? Image: Completed? Securely seal the lower end of the vapor piping inside the dispenser cabinet using only threaded Image: Completed?	Facility's Legal Name:							
Facility Address: Owner/Operator Information (Facility Contact) Name: Email Address: Telephone No.: Mailing Address: Stage II Decommissioning Activity Checklist Y N N Relieve pressure in the tank ullage by removing all pressure/vacuum vent valves. Image: Completed? Y N N Drain all liquid collection points and vapor pumps for individual dispensers. Image: Completed? Y N N Beinove all centrally located vapor pumps; Image: Completed? Y N N Disconnect all electrical components of the Stage II system so that no electrical hazards are created. Image: Completed? Image: Completed? Securely seal the below-grade vapor piping at a height below the level of the base of the dispenser Image: Completed? Image: Completed? Securely seal the below-grade vapor oping at a height below the level of the base of the dispenser Image: Completed? Image: Completed? Securely seal the below-erade vapor piping at the tank top if this can be done without excavation and without interfering with the vent line using only threaded plugs, threaded caps, or glue fittings. Image: Completed? Image: Completed? Securely seal the lower end of the vapor piping inside the dispenser cabinet using only threaded Image: Completed?	Facility's Local Name							
Owner/Operator Information (Facility Contact) Name: Email Address: Telephone No.: Mailing Address: Stage II Decommissioning Activity Checklist Completed? Y N N/A Relieve pressure in the tank ullage by removing all pressure/vacuum vent valves.	Facility's Local Name.							
Owner/Operator Information (Facility Contact) Name: Email Address: Telephone No.: Mailing Address: Stage II Decommissioning Activity Checklist Completed? Y N N/A Relieve pressure in the tank ullage by removing all pressure/vacuum vent valves.	Facility Address:							
Name: Email Address: Telephone No.: Mailing Address: Completed? Y N Stage II Decommissioning Activity Checklist Y Relieve pressure in the tank ullage by removing all pressure/vacuum vent valves.								
Mailing Address: Completed? Y N N/A Relieve pressure in the tank ullage by removing all pressure/vacuum vent valves.	Owner/Operator Information (Facility Contact)							
Completed? Y N Relieve pressure in the tank ullage by removing all pressure/vacuum vent valves.	Name:	Email Address:	Telephone No.:					
Completed? Y N Relieve pressure in the tank ullage by removing all pressure/vacuum vent valves.								
Stage II Decommissioning Activity CnecklistYNN/ARelieve pressure in the tank ullage by removing all pressure/vacuum vent valves	Mailing Address:							
Stage II Decommissioning Activity CnecklistYNN/ARelieve pressure in the tank ullage by removing all pressure/vacuum vent valves					Completed?			
Relieve pressure in the tank ullage by removing all pressure/vacuum vent valves. □ □ Drain all liquid collection points and vapor pumps for individual dispensers. □ □ Remove all centrally located vapor pumps; □ □ □ Disconnect all electrical components of the Stage II system so that no electrical hazards are created. □ □ □ e.g., all vapor pumping or processing units and dispenser electronics □ □ □ Securely seal the below-grade vapor piping at a height below the level of the base of the dispenser using only threaded plugs, threaded caps, or glued fittings. □ □ Disconnect and seal off the vapor piping at the tank top if this can be done without excavation and without interfering with the vent line using only threaded plugs, threaded caps, or glue fittings. □ □ Securely seal the lower end of the vapor piping inside the dispenser cabinet using only threaded plugs, threaded caps, or glue fittings. □ □ Replace the stage II hanging hardware including hoses, nozzles, swivels, and breakaway components with conventional, industry-standard hanging hardware. □ □ Install appropriate pressure/vacuum vent valve(s) or cap(s). □ □ □ Remove any Stage II instructions from the dispenser cabine	Stage II Decommissioning Activity Checklist				•			
Remove all centrally located vapor pumps;	Relieve pressure in the tank ullage by removing all pressure/vacuum vent valves.							
Disconnect all electrical components of the Stage II system so that no electrical hazards are created. Image: Components of the Stage II system so that no electrical hazards are created. e.g., all vapor pumping or processing units and dispenser electronics Image: Components of the Stage II vapor recovery is no longer in service. Reprogram the dispenser electronics to reflect that Stage II vapor recovery is no longer in service. Image: Components of the vapor piping at a height below the level of the base of the dispenser using only threaded plugs, threaded caps, or glued fittings. Disconnect and seal off the vapor piping at the tank top if this can be done without excavation and without interfering with the vent line using only threaded plugs, threaded caps, or glue fittings. Image: Components of the vapor piping inside the dispenser cabinet using only threaded plugs, threaded caps, or glue fittings. Securely seal the lower end of the vapor piping inside the dispenser cabinet using only threaded plugs, threaded caps, or glue fittings. Image: Components of the vapor piping inside the dispenser cabinet using only threaded plugs, threaded caps, or glue fittings. Replace the stage II hanging hardware including hoses, nozzles, swivels, and breakaway components with conventional, industry-standard hanging hardware. Image: Component value(s) or cap(s). Remove any Stage II instructions from the dispenser cabinet. Image: Component of the vapor recovery. Image: Component of the vapor recovery. Disconnect the central vacuum motor if present on the Stage II system and seal piping using only threaded plugs, threaded caps, or glue fittings. <td colspan="3"></td> <td></td> <td></td> <td></td>								
e.g., all vapor pumping or processing units and dispenser electronics Image: Construction of the storage system are left in a condition that will reliably prevent the release of any vapors or liquids from any component of the storage system associated with Stage II vapor recovery.								
e.g., all vapor pumping or processing units and dispenser electronics Image: Construction of the storage system are left in a condition that will reliably prevent the release of any vapors or liquids from any component of the storage system are left in a conduct a plugs, threaded caps, or glue fittings.						_		
Securely seal the below-grade vapor piping at a height below the level of the base of the dispenser using only threaded plugs, threaded caps, or glued fittings. Disconnect and seal off the vapor piping at the tank top if this can be done without excavation and without interfering with the vent line using only threaded plugs, threaded caps, or glue fittings. Securely seal the lower end of the vapor piping inside the dispenser cabinet using only threaded plugs, threaded caps, or glue fittings. Replace the stage II hanging hardware including hoses, nozzles, swivels, and breakaway components with conventional, industry-standard hanging hardware. Install appropriate pressure/vacuum vent valve(s) or cap(s). Remove any Stage II instructions from the dispenser cabinet. Conduct a visual check to verify that the visible components of the storage system are left in a condition that will reliably prevent the release of any vapors or liquids from any component of the storage system associated with Stage II vapor recovery. Disconnect the central vacuum motor if present on the Stage II system and seal piping using only threaded plugs, threaded caps, or glue fittings. 								
using only threaded plugs, threaded caps, or glued fittings	Reprogram the dispenser electronics to reflect that Stage II vapor recovery is no longer in service.							
using only threaded plugs, threaded caps, or glued fittings	Securely seal the below-grade vapor piping at a height below the level of the base of the dispenser							
without interfering with the vent line using only threaded plugs, threaded caps, or glue fittings.ISecurely seal the lower end of the vapor piping inside the dispenser cabinet using only threaded plugs, threaded caps, or glue fittings.IReplace the stage II hanging hardware including hoses, nozzles, swivels, and breakaway components with conventional, industry-standard hanging hardware.IInstall appropriate pressure/vacuum vent valve(s) or cap(s).IRemove any Stage II instructions from the dispenser cabinet.IConduct a pressure decay test.IConduct a visual check to verify that the visible components of the storage system are left in a condition that will reliably prevent the release of any vapors or liquids from any component of the storage system associated with Stage II vapor recovery.Disconnect the central vacuum motor if present on the Stage II system and seal piping using only threaded plugs, threaded caps, or glue fittings.								
without interfering with the vent line using only threaded plugs, threaded caps, or glue fittings.Image: Constant of the vapor piping inside the dispenser cabinet using only threaded plugs, threaded caps, or glue fittings.Securely seal the lower end of the vapor piping inside the dispenser cabinet using only threaded plugs, threaded caps, or glue fittings.Image: Constant of the vapor piping inside the dispenser cabinet using only threaded plugs, threaded caps, or glue fittings.Replace the stage II hanging hardware including hoses, nozzles, swivels, and breakaway components with conventional, industry-standard hanging hardware.Image: Constant of the vapor piping inside the dispenser cabinet.Install appropriate pressure/vacuum vent valve(s) or cap(s).Image: Conduct a pressure decay test.Image: Conduct a pressure decay test.Conduct a visual check to verify that the visible components of the storage system are left in a condition that will reliably prevent the release of any vapors or liquids from any component of the storage system associated with Stage II vapor recovery.Image: Conduct a value of the vacuum motor if present on the Stage II system and seal piping using only threaded plugs, threaded caps, or glue fittings.								
plugs, threaded caps, or glue fittings	without interfering with the vent line using only threaded plugs, threaded caps, or glue fittings.							
Replace the stage II hanging hardware including hoses, nozzles, swivels, and breakaway components with conventional, industry-standard hanging hardware.Image: Image: Ima								
with conventional, industry-standard hanging hardware.Install appropriate pressure/vacuum vent valve(s) or cap(s).Install appropriate pressure/vacuum vent valve(s) or cap(s).Image: Image:								
Install appropriate pressure/vacuum vent valve(s) or cap(s). Image: Conduct a pressure decay test. Image: Conduct a pressure decay test. Conduct a pressure decay test. Image: Conduct a visual check to verify that the visible components of the storage system are left in a condition that will reliably prevent the release of any vapors or liquids from any component of the storage system associated with Stage II vapor recovery. Image: Conduct a visual check to verify that the visible components of the storage system are left in a condition that will reliably prevent the release of any vapors or liquids from any component of the storage system associated with Stage II vapor recovery. Disconnect the central vacuum motor if present on the Stage II system and seal piping using only threaded plugs, threaded caps, or glue fittings. Image: Conduct a visual check caps and vapor seal piping using only threaded plugs.								
Remove any Stage II instructions from the dispenser cabinet. Image: Conduct a pressure decay test. Image: Conduct a pressure decay test. Conduct a visual check to verify that the visible components of the storage system are left in a condition that will reliably prevent the release of any vapors or liquids from any component of the storage system associated with Stage II vapor recovery. Image: Image: Conduct a pressure decay test. Disconnect the central vacuum motor if present on the Stage II system and seal piping using only threaded plugs, threaded caps, or glue fittings. Image: Image: Image: Conduct a pressure decay test and pre								
Conduct a pressure decay test.Image: Conduct a visual check to verify that the visible components of the storage system are left in a condition that will reliably prevent the release of any vapors or liquids from any component of the storage system associated with Stage II vapor recovery.Image: Image: I								
Conduct a visual check to verify that the visible components of the storage system are left in a condition that will reliably prevent the release of any vapors or liquids from any component of the storage system associated with Stage II vapor recovery.Image: Image: Imag								
condition that will reliably prevent the release of any vapors or liquids from any component of the storage system associated with Stage II vapor recovery.Image: Image:	· · ·							
storage system associated with Stage II vapor recovery.Image: Storage system associated with Stage II vapor recovery.Disconnect the central vacuum motor if present on the Stage II system and seal piping using only threaded plugs, threaded caps, or glue fittings.Image: Image:								
Disconnect the central vacuum motor if present on the Stage II system and seal piping using only threaded plugs, threaded caps, or glue fittings.								
threaded plugs, threaded caps, or glue fittings.								
	All gasoline pumps were removed or replaced with pumps that do not have Stage II equipment.							

Decommissioning Date

Documentation of the Stage II decommissioning activity must be submitted with this form. Documentation may include a copy of any contracts, work orders, certifications, or receipts for decommissioning equipment.

Completion date:

Contractor Information					
Name:	Email Address:	Telephone No.:			
Company Name:					

Pursuant to La. R.S. 30:2025, any willfully or knowingly false statement, representation, or certification in any form, application, record, label, manifest, report, plan, or other document submitted to the Department may be subject to civil or criminal penalties. I certify that the information contained in this form is true and accurate to the best of my knowledge.

Signature of Responsible Official

Date

Print Name

Title